Introduction of MingTyan Co. Ltd.

明田鐵工廠股份有限公司設立於1973年,數十多年來一直堅持提供客戶優良品質與服務至上的理念,將各種空氣壓縮機產品行銷至國內外各地。在產品開發上,明田以優質元件和嚴格的品質管制程序,在空壓機產品上維持歷久不變的優良品質;且以先進設備與技術,不斷為客戶開發新型適切之產品型式;在客戶服務方面,有精良的工程師協助產品的解說與維修服務,提供客戶多元產品資訊。明田公司秉持一貫的理念,以高品質的產品和效率的服務,持續為顧客提供最佳解決方案。

MingTyan Iron Works Co. Ltd. established in 1973. In the past decades, MingTyan has insisted its core business concept in providing high quality air compressors and customer-oriented service for all the clients in Taiwan and international markets. In product development, MingTyan produces various types of air compressors with high-quality components and materials. Keeping the strict operating and quality control process, MingTyan stands in an advantageous position in the industry. Additionally, MingTyan also keeps upgrading equipment and technologies to develop new types of air compressors for customers' wider applications. In service, MingTyan's engineers always help customers to get knowledge in all products information and offer efficient after-sale service. Based on the core business concept, high-quality products and customer-oriented services, MingTyan looks for the best solution in different demands of all customers.

無油式空機機

Direct Drive Oil-less Air-Compressor

Direct Drive Oil-less Air Compressor is relatively light and easy to carry with a good quality price ratio. The product can easily to start at a low temperature in a wide range of accessories. There is no maintenance required in this the oil-less design type. This type is also fit for using DIY purpose at home.

- Light and easy to carry
- No maintenance required
- Started with a low temperature in a wide-range applications
- Idea for household for DIY







| 型 號 | 馬 | カ | 氣 缸 數 | 使用 | 壓力 | 最高 | 壓力 | 空壓機轉數 | 排氣 | 貳量 | 氣 桶 | 容量 | 尺寸 | 重量 |
|-----------|-----|------|----------|--------------------|-----|--------------------|-----|-------|-------|-----|-----|------|---------------|------|
| MODEL | HP | KW | Cylinder | Kg/cm ² | psi | Kg/cm ² | psi | R.P.M | ℓ/min | CFM | Ł | Gal. | L x W x H(cm) | kg |
| VIOF-2012 | 2 | 1.5 | 1 | 8 | 115 | 10 | 145 | 1720 | 155 | 5.5 | 12 | 3.2 | 47x 25x 55 | 25 |
| VIOF-2525 | 2.5 | 1.75 | 1 | 8 | 115 | 10 | 145 | 1720 | 170 | 6 | 25 | 6.6 | 59x 33x 60 | 27 |
| VIOF-4050 | 4.5 | 3.3 | 2 | 8 | 115 | 10 | 145 | 1720 | 340 | 12 | 50 | 13.2 | 69x 38x 65 | 46.5 |

直接式空壓機

Direct Drive Air-Compressor

Direct Drive Air Compressor is designed for applying with a wide range of accessories and pneumatic tools. This type, long life with a low rpm, provides a very high efficiency and fast performance in different semi-professional applications, including large-size pneumatic tools. Direct Drive Air Compressor is also ideal for using at household for DIY as the design is easy for move.

- Powerful, reliable, and fast
- Long life with a low rpm
- High efficiency for heavy-duty usage Suitable for large-size pneumatic tools and semi-professional purpose
- Idea for household for DIY

| 型 號 | 馬 | カ | 氣缸 數 | 使用壓力 | | 最高 | 壓力 | 空壓機轉數 | 排象 | 貳量 | 氣 桶 | 容量 | 尺寸 | 重量 |
|-----------|-----|------|----------|--------------------|-----|--------|-----|-------|-------|------|-----|------|---------------|------|
| MODEL | HP | KW | Cylinder | Kg/cm ² | psi | Kg/cm² | psi | R.P.M | ℓ/min | CFM | Ł | Gal. | L x W x H(cm) | kg |
| VI-1506 | 1.5 | 1.1 | 1 | 8 | 115 | 10 | 145 | 3450 | 143 | 5.1 | 6 | 1.6 | 46x 19x 41 | 14.0 |
| VI-1508 | 2 | 1.1 | 1 | 8 | 115 | 10 | 145 | 3450 | 143 | 5.1 | 8 | 2.1 | 48x 19x 43 | 14.5 |
| VI-200801 | 2.5 | 1.75 | 1 | 8 | 115 | 10 | 145 | 3450 | 180 | 6.4 | 8 | 2.1 | 48x 19x 43 | 16.5 |
| VI-200802 | 2.5 | 1.75 | 1 | 8 | 115 | 10 | 145 | 3450 | 180 | 6.4 | 8 | 2.1 | 36x 29x 44 | 17.0 |
| VI-201601 | 2.5 | 1.75 | 1 | 8 | 115 | 10 | 145 | 3450 | 180 | 6.4 | 16 | 2.1 | 55x 33x 49 | 19.0 |
| VI-201602 | 2.5 | 1.75 | 1 | 8 | 115 | 10 | 145 | 3450 | 180 | 6.4 | 16 | 2.1 | 55x 33x 47 | 19.5 |
| VI-1010 | 1 | 0.75 | 1 | 8 | 115 | 10 | 145 | 1720 | 100 | 3.5 | 10 | 2.6 | 44x 32x 60 | 22 |
| VI-1025 | 1 | 0.75 | 1 | 8 | 115 | 10 | 145 | 1720 | 100 | 3.5 | 25 | 2.6 | 55x 30x 60 | 26 |
| VI-1525 | 1.5 | 1.1 | 1 | 8 | 115 | 10 | 145 | 1720 | 125 | 4.4 | 25 | 6.6 | 55x 30x 60 | 26 |
| VI-2025 | 2 | 1.5 | 1 | 8 | 115 | 10 | 145 | 1720 | 155 | 5.5 | 25 | 6.6 | 55x 30x 60 | 28 |
| VI-2525 | 2.5 | 1.9 | 1 | 8 | 115 | 10 | 145 | 1720 | 170 | 6.0 | 25 | 6.6 | 55x 30x 60 | 28 |
| VI-3530 | 3.5 | 2.6 | 2 | 8 | 115 | 10 | 145 | 1720 | 260 | 9.2 | 30 | 7.9 | 67x 32x 60 | 38 |
| VI-3550 | 3.5 | 2.6 | 2 | 8 | 115 | 10 | 145 | 1720 | 260 | 9.2 | 50 | 13.2 | 69x 38x 66 | 45 |
| VI-4050 | 4.5 | 3.3 | 2 | 8 | 115 | 10 | 145 | 1720 | 310 | 10.9 | 50 | 13.2 | 69x 38x 66 | 49 |
| VI-35100 | 3.5 | 2.6 | 2 | 8 | 115 | 10 | 145 | 1720 | 260 | 9.2 | 100 | 26.4 | 80x 48x 75 | 68 |
| VI-45100 | 4.5 | 3.3 | 2 | 8 | 115 | 10 | 145 | 1720 | 310 | 10.9 | 100 | 26.4 | 70x 48x 75 | 74 |



18.

VI-1010

VIVA OIL



VI-1025



VI-1525



VI-3550



VI-45100



WI WAAI

VI-1506

皮带式空壓機

Single Stage Belt Drive Air Compressor

Single Stage Belt Drive Air Compressor provides a high efficient work performance in a wide range of applications. The design is powerful, safe, and long life with a low rpm. The type is reliable for heavy-duty usage. This Belt Drive Air Compressor also ideal for indoor decoration work, craftsmen, and small-medium workshops.

- Powerful, safe, long life, and low rpm
- High efficiency for heavy-duty usage
- Suitable for small-medium size workspace
- Fit for indoor decoration and craftsmen

| 型 號 | 馬 | カ | 氣 缸 數 | 使用 | 壓力 | 最高 | 壓力 | 空壓機轉數 | 排象 | 貳量 | 氣 桶 | 容量 | 尺寸 | 重量 |
|---------|-----|------|----------|--------------------|-----|--------|-----|-------|-------|-----------|-----|-------|---------------|-----|
| MODEL | HP | KW | Cylinder | Kg/cm ² | psi | Kg/cm² | psi | R.P.M | ℓ/min | CFM | Ł | Gal. | L x W x H(cm) | kg |
| MT-10PL | 1/4 | 0.2 | 1 | 8 | 115 | 10 | 145 | 750 | 60 | 2.1 | 36 | 9.5 | 76x 31x 58 | 35 |
| MT-11P | 1/2 | 0.4 | 1 | 8 | 115 | 10 | 145 | 1200 | 128 | 4.5 | 40 | 10.6 | 78x 33x 64 | 40 |
| MT-21P | 1/2 | 0.4 | 2 | 8 | 115 | 10 | 145 | 780 | 147 | 5.2 | 58 | 15.3 | 91x 39x 67 | 58 |
| MT-22P | 1 | 0.75 | 2 | 8 | 115 | 10 | 145 | 800 | 185 | 6.5 | 88 | 23.2 | 100x 42x 77 | 85 |
| MT-23P | 2 | 1.5 | 2 | 8 | 115 | 10 | 145 | 900 | 300 | 10.6 | 95 | 25.1 | 108x 42x 78 | 97 |
| MT-23WP | 2 | 1.5 | 3 | 8 | 115 | 10 | 145 | 670 | 300 | 10.6 | 95 | 25.1 | 108x 42x 80 | 105 |
| MT-31P | 3 | 2.2 | 2 | 8 | 115 | 10 | 145 | 770 | 464 | 16.4 | 110 | 29.1 | 114x 47x 89 | 150 |
| MT-51WP | 5 | 3.7 | 3 | 8 | 115 | 10 | 145 | 850 | 769 | 27.2 | 155 | 41.0 | 146x 51x 103 | 205 |
| MT-275P | 7.5 | 5.5 | 2 | 8 | 115 | 10 | 145 | 950 | 1045 | 36.9 | 245 | 64.7 | 149x 65x 118 | 310 |
| MT-310P | 10 | 7.5 | 3 | 8 | 115 | 10 | 145 | 900 | 1484 | 52.4 | 300 | 79.3 | 175x 65x 118 | 350 |
| MT-315P | 15 | 11 | 3 | 8 | 115 | 10 | 145 | 860 | 2334 | 82.4 | 300 | 79.3 | 175x 67x 128 | 420 |
| MT-220P | 20 | 15 | 2 | 8 | 115 | 10 | 145 | 650 | 3167 | 111.9 | 420 | 111.0 | 176x 84x 159 | 560 |





MT-22P



MT-51WP



MT-275P



高壓式空壓機

Two Stage Belt Drive Air Compressor

Two Stage Belt Drive Air Compressor is designed for the professional use in heavy-duty situation. With a high efficiency, the type is suitable for industrial applications and special pneumatic tools, e.g. truck tire inflator. This series of type include belt-drive or engine designs.

- Very powerful and high efficiency
- Suitable for heavy-duty usage
- Ideal for professional special pneumatic tools
- Suitable for different industrial applications



HMT-310P







HMT-31P

| 型號 | 馬 | カ | 氣 缸 數 | 使用 | 壓力 | 最高 | 壓力 | 空壓機轉數 | 排氣 | 貳量 | 氣 桶 | 容量 | 尺寸 | 重量 |
|-----------|-----|-----|----------|--------------------|-----|--------------------|-----|-------|-------|------|-----|------|---------------|-----|
| MODEL | HP | KW | Cylinder | Kg/cm ² | psi | Kg/cm ² | psi | R.P.M | ℓ/min | CFM | £ | Gal. | L x W x H(cm) | kg |
| HMT-23WP | 2 | 1.5 | 3 | 12 | 175 | 16 | 230 | 800 | 225 | 7.9 | 95 | 25.1 | 104x 39x 80 | 110 |
| HMT-31P | 3 | 2.2 | 2 | 12 | 175 | 16 | 230 | 950 | 303 | 10.7 | 110 | 29.1 | 114x 47x 89 | 155 |
| HMT-51WP | 5 | 3.7 | 3 | 12 | 175 | 16 | 230 | 950 | 572 | 20.2 | 155 | 41.0 | 146x 51x 103 | 210 |
| HMT-275WP | 7.5 | 5.5 | 2 | 12 | 175 | 16 | 230 | 750 | 825 | 29.1 | 245 | 64.7 | 149x 65x 118 | 315 |
| HMT-310P | 10 | 7.5 | 3 | 12 | 175 | 16 | 230 | 990 | 1088 | 38.4 | 300 | 79.3 | 175x 65x 118 | 355 |
| HMT-315P | 15 | 11 | 2 | 12 | 175 | 16 | 230 | 860 | 1566 | 55.3 | 300 | 79.3 | 175x 67x 118 | 430 |

引擎式空壓機

Engine Type Air compressor

Engine Type Air Compressor drives with engine and can be used in an environment without electricity. The type works with petroleum or diesel. It is ideal for a wide range of industrial applications and profession purposes, e.g. the applications in agriculture. The design is mobile, and can be worked for remote area application .

- Ideal for using in an environment without electricity
- Working with petroleum or diesel
- Suitable for all applications in different industries
- Ideal for professional purposes



HMT-51WD



MT-21G

| 型號 | 馬力 | 氣 缸 數 | 使用 | 壓力 | 最高 | 壓力 | 空壓機轉數 | 排氣 | 貳量 | 氣 桶 | 容量 | 尺寸 | 重量 |
|----------|------|----------|--------|-----|--------|-----|-------|-------|-----------|-----|------|---------------|-----|
| MODEL | HP | Cylinder | Kg/cm² | psi | Kg/cm² | psi | R.P.M | ℓ/min | CFM | Ł | Gal. | L x W x H(cm) | kg |
| MT-21G | 4 | 2 | 8 | 115 | 10 | 145 | 900 | 165 | 5.8 | 40 | 10.6 | 88x 43x 70 | 57 |
| MT-23G | 6 | 2 | 8 | 115 | 10 | 145 | 900 | 300 | 10.6 | 95 | 25.1 | 117x 49x 85 | 85 |
| MT-31D | 6 | 2 | 8 | 115 | 10 | 145 | 770 | 460 | 16.4 | 110 | 29.1 | 135x 50x 96 | 190 |
| MT-51WD | 10.5 | 3 | 8 | 115 | 10 | 145 | 850 | 769 | 27.2 | 155 | 41.0 | 146x 65x 112 | 275 |
| MT-275D | 13 | 2 | 8 | 115 | 10 | 145 | 950 | 1045 | 36.9 | 245 | 64.7 | 165x 70x 115 | 345 |
| MT-310D | 18 | 3 | 8 | 115 | 10 | 145 | 900 | 1484 | 52.4 | 300 | 79.3 | 190x 76x 121 | 420 |
| HMT-23WG | 6 | 2 | 12 | 175 | 16 | 230 | 800 | 255 | 9.0 | 95 | 25.1 | 117x 49x 85 | 90 |
| HMT-31D | 6 | 2 | 12 | 175 | 16 | 230 | 950 | 303 | 10.7 | 110 | 29.1 | 135x 50x 96 | 190 |
| HMT-51WD | 10.5 | 3 | 12 | 175 | 16 | 230 | 950 | 575 | 20.2 | 155 | 41.0 | 146x 65x 112 | 275 |
| HMT-275D | 13 | 2 | 12 | 175 | 16 | 230 | 750 | 825 | 29.1 | 245 | 64.7 | 165x 70x 115 | 345 |
| HMT-310D | 18 | 3 | 12 | 175 | 16 | 230 | 990 | 1088 | 38.4 | 300 | 79.3 | 190x 76x 121 | 420 |
| HMT-51HD | 10.5 | 2 | 16 | 230 | 20 | 290 | 700 | 573 | 20.2 | 245 | 64.7 | 146x 65x 112 | 305 |

「箱型靜音式空壓機

Silent Type Air compressor

Silent Type Air Compressor with a compact and lean design works with a low level of volume. This type can be applied with different accessories. With a box-outlook and quiet operation, it is ideal to maintain and use in residential area. The noise level is under 70dB.

- Compact and lean design
- Quiet with a low level of volume
- Easy and simple maintenance
- Ideal for using in residential area



SMT-300/500/750/1000

規格 / Specification

| 型 號 | 馬 | カ | 氣 缸 數 | 使用壓力 | | 最高 | 壓力 | 空壓機轉數 | 排氣量 | | 尺寸 | 重量 |
|----------|-----|-----|----------|--------------------|-----|--------------------|-----|-------|-------|------|---------------|-----|
| MODEL | HP | KW | Cylinder | Kg/cm ² | psi | Kg/cm ² | psi | R.P.M | ℓ/min | CFM | L x W x H(cm) | kg |
| SMT-200 | 2 | 1.5 | 1 | 8 | 115 | 10 | 145 | 1720 | 170 | 6 | 68x 43x 79 | 64 |
| SMT-300 | 3 | 2.2 | 2 | 8 | 115 | 10 | 145 | 770 | 464 | 16.4 | 86x 75x 105 | 160 |
| SMT-500 | 5 | 3.7 | 3 | 8 | 115 | 10 | 145 | 850 | 769 | 27.2 | 86x 75x 105 | 280 |
| SMT-750 | 7.5 | 5.5 | 2 | 8 | 115 | 10 | 145 | 950 | 1045 | 36.9 | 95x 85x 133 | 320 |
| SMT-1000 | 10 | 7.5 | 3 | 8 | 115 | 10 | 145 | 900 | 1484 | 52.4 | 95x 85x 133 | 370 |

直流電用空壓機

DC Type Air compressor

DC type Air Compressor has a small-size design that is easy to carry and operate for outdoor activities. With the electricity connection to automobile, this type provides customers to use in outdoor demand. As this type is relative small, it is proper for the clients who works for light-duty purpose.

- Especially design for light-duty purpose
- Easy to carry
- Suitable for using in outdoor
- Compatible to connect electricity from automobile



| 型號 | 馬 | カ | 氣 缸 數 | 使用 | 壓力 | 最高 | 壓力 | 空壓機轉數 | 排氣 | 貳 量 | 氣 桶 | 容量 | 尺寸 | 重量 |
|-------|----|------|----------|--------------------|-----|--------|-----|-------|-------|-----|-----|------|---------------|----|
| MODEL | HP | KW | Cylinder | Kg/cm ² | psi | Kg/cm² | psi | R.P.M | ℓ/min | CFM | £ | Gal. | L x W x H(cm) | kg |
| DC12V | 1 | 0.75 | 1 | 8 | 115 | 10 | 145 | 2850 | 116 | 4.1 | 8 | 2.1 | 49x 19x 45 | 14 |
| DC24V | 1 | 0.75 | 1 | 8 | 115 | 10 | 145 | 2850 | 116 | 4.1 | 8 | 2.1 | 49x 19x 45 | 14 |

儲氣桶

Vertical Air Tanks

MingTyan offers a range of vertical air receivers from 88 to 660 litres that are suitable for different industrial air compressed systems. The product is supplied with all necessary fittings. When applying vertical air receiver in your system, the system creates higher air consumption capacity than compressor as it works like a buffer allowing the distribution system for air temporarily.

- Unique design with twin tank and lower height
- High efficiency
- Easy to carry
- Ideal for all applications in accessories and pneumatic tools

規格 / Specification

| 型 號 | 氣 桶 | 容量 | 尺寸 | 重量 |
|-------|-------|------|---------------|-----|
| MODEL | Liter | Gal. | L x W x H(cm) | kg |
| T-88 | 88 | 23 | 50x 50x 110 | 36 |
| T-110 | 110 | 29 | 50x 50x 130 | 50 |
| T-155 | 155 | 41 | 55x 55x 150 | 72 |
| T-240 | 240 | 64 | 65x 65x 155 | 118 |
| T-360 | 360 | 95 | 75x 75x 160 | 152 |
| T-460 | 460 | 121 | 75x 75x 190 | 185 |
| T-660 | 660 | 160 | 95x 95x 190 | 225 |



乾 燥 機

Air Dryer

The product is designed for pursuit a perfect quality air when users apply in special circumstances. Connecting to the product, spray paint operations, laboratories and certain printing and pneumatic tool users can get a perfect performance. Customers could also select the right systems by combing certain compressors and auxiliary equipment. The optional multiple control model is advanced option for specific need. The product can also supply clean air free of moisture and oil when combining an oil-free compressor.



| 型號 | 處理空 | 空氣量 | 出入口管 | 尺寸 | 重量 | 消費電量 | 電源 |
|---------|---------|------|--------|---------------|-----|------|----------|
| MODEL | Nm³/min | SCFM | 管徑 | L x W x H(cm) | kg | kw | 60Hz/V |
| MT-5AC | 8.0 | 28 | G1/2" | 55x 38x 65 | 56 | 0.6 | 220V/IPh |
| MT-10AC | 1.35 | 47 | G1" | 73x 49x 72 | 68 | 0.7 | 220V/IPh |
| MT-20AC | 2.6 | 91 | G11/4" | 82x 49x 75 | 90 | 1.0 | 220V/IPh |
| MT-30AC | 3.6 | 127 | G1½" | 107x 60x 90 | 140 | 1.3 | 220V/IPh |
| MT-50AC | 6.9 | 243 | G2" | 107x 60x 90 | 150 | 1.8 | 220V/IPh |